UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/618,699	07/15/2003	Masaya Tamaru	0649-0900P	4919
2292 7590 05/04/2007 BIRCH STEWART KOLASCH & BIRCH PO BOX 747			EXAMINER	
			· YODER III, CHRISS S	
FALLS CHURCH, VA 22040-0747		ART UNIT	PAPER NUMBER	
			2622	
			NOTIFICATION DATE	DELIVERY MODE
			05/04/2007	ELECTRONIC

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

mailroom@bskb.com

	Application No.	Applicant(s)				
	10/618,699	TAMARU ET AL.				
Office Action Summary	Examiner	Art Unit				
	Chriss S. Yoder, III	2622				
The MAILING DATE of this communication app Period for Reply	ears on the cover sheet with the c	orrespondence address				
A SHORTENED STATUTORY PERIOD FOR REPLY WHICHEVER IS LONGER, FROM THE MAILING DA - Extensions of time may be available under the provisions of 37 CFR 1.13 after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period w - Failure to reply within the set or extended period for reply will, by statute, Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION 36(a). In no event, however, may a reply be tim vill apply and will expire SIX (6) MONTHS from cause the application to become ABANDONEI	l. ely filed the mailing date of this communication. O (35 U.S.C. § 133).				
Status						
1) Responsive to communication(s) filed on 05 Fe	ebruary 2007.					
3) Since this application is in condition for allowar	Since this application is in condition for allowance except for formal matters, prosecution as to the merits is					
closed in accordance with the practice under Ex parte Quayle, 1935 C.D. 11, 453 O.G. 213.						
Disposition of Claims						
4) Claim(s) <u>1-3</u> is/are pending in the application. 4a) Of the above claim(s) is/are withdray 5) Claim(s) is/are allowed. 6) Claim(s) <u>1-3</u> is/are rejected. 7) Claim(s) is/are objected to. 8) Claim(s) are subject to restriction and/or						
Application Papers						
9) ☐ The specification is objected to by the Examine 10) ☑ The drawing(s) filed on 15 July 2003 is/are: a) ☐ Applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11) ☐ The oath or declaration is objected to by the Ex	☑ accepted or b)☐ objected to b drawing(s) be held in abeyance. See ion is required if the drawing(s) is obj	ected to. See 37 CFR 1.121(d).				
Priority under 35 U.S.C. § 119						
12) ☑ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a) ☑ All b) ☐ Some * c) ☐ None of: 1. ☑ Certified copies of the priority documents have been received. 2. ☐ Certified copies of the priority documents have been received in Application No 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)). * See the attached detailed Office action for a list of the certified copies not received.						
Attachment(s) 1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date	4) Interview Summary Paper No(s)/Mail Da 5) Notice of Informal P 6) Other:	te				

DETAILED ACTION

Response to Arguments

Applicant's arguments filed February 5, 2007 have been fully considered but they are not persuasive.

Applicant argues that in Jones, only green pixels have different sensitivities, i.e. a number of green pixels having a first sensitivity G_1 and a number of green pixels having a second sensitivity G_2 , and thus for all pixels of the solid-state image pickup device, each pixel does **not** include a high-sensitivity pixel and a low-sensitivity pixel with each high-sensitivity pixel and each low-sensitivity pixel being unique to that pixel. In response to applicant's argument that the references fail to show certain features of applicant's invention, it is noted that the features upon which applicant relies (i.e., each pixel includes a high-sensitivity pixel and a low-sensitivity pixel) are not recited in the rejected claim(s). Although the claims are interpreted in light of the specification, limitations from the specification are not read into the claims. See *In re Van Geuns*, 988 F.2d 1181, 26 USPQ2d 1057 (Fed. Cir. 1993). The Examiner points out that the claims simply recite an image pickup component having high and low sensitivity pixels, and nothing regarding each pixel having a high and low sensitivity pixel.

Applicant also argues, that neither Serizawa, Jones nor Skow disclose or suggest that a photometric characteristic of an output of the high-sensitivity pixels being different from that of the low-sensitivity pixels, or that an exposure value is calculated based on values of signal detected by the high-sensitivity pixels and values of signal detected by the low-sensitivity pixels, which are output from the solid-state image pickup

device in a single instance of photometry. As for the argument that a photometric characteristic of an output of the high-sensitivity pixels being different from that of the low-sensitivity pixels is not disclosed/suggested, the Examiner notes that Jones was relied upon to teach the use of high-sensitivity and low-sensitivity pixels (column 4, lines 3-35), wherein high and low sensitivity pixels inherently have different photometric characteristics. And as for the argument that an exposure value is calculated based on values of signal detected by the high-sensitivity pixels and values of signal detected by the low-sensitivity pixels, which are output from the solid-state image pickup device in a single instance of photometry. First the Examiner points out that the limitation of "a single instance of photometry" is interpreted to encompass the entire process of photometry (i.e., all of the steps used in the process of calculating a photometry/exposure value). And with respect to the references, Serizawa and Skow are relied upon to teach the use of an image signal being used to calculate an exposure value; and Jones is relied upon to modify Serizawa in claim 1, so as to provide high and low sensitivity pixels picking up different exposure levels within the same image in order to capture a single image instead of two, thereby reducing the amount of memory needed and to reduce the effects of changes in the scene that occur between capturing the two images (Jones: column 1, lines 52-65), and to modify Skow in claims 2-3, so as to provide high-sensitivity pixels and low-sensitivity pixels forming the solid-state image pickup in order to capture an image having a high dynamic range so that all areas of the image, including light areas and dark areas are captured sufficiently (column 1, lines 28-40). Therefore, by using high and low sensitivity pixels to output an image as

suggested by Jones to be used by Serizawa/Skow to calculate the exposure values based on the picked up image signal, the limitations are met.

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

- (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 1. Claim 1 is rejected under 35 U.S.C. 103(a) as being unpatentable over Serizawa et al (US Patent # 6,593,970) in view of Jones (US Patent # 6,924,841).
- 2. In regard to claim 1, note Serizawa discloses the use of an image pickup apparatus, comprising a solid-state image pickup device having pixels (column 8, lines 12-20 and figure 1: 1010), control means for calculating an exposure value based on values of signal detected by said pixels, which are output from said solid-state image pickup device in a single instance of photometry (column 8, lines 41-67), and signal processing means for reading data of an image picked up by said solid-state image pickup device and processing according to the exposure value (column 8, lines 41-67).

Therefore, it can be seen that the Serizawa device lacks the use of high-sensitivity pixels and low-sensitivity pixels forming the solid-state image pickup and that the exposure value is calculated based on values of signal detected by the high-sensitivity pixels and values of signal detected by the low-sensitivity pixels, wherein a photometric characteristic of an output of the high-sensitivity pixels being different from

Application/Control Number: 10/618,699

Art Unit: 2622

that of the low-sensitivity pixels. Jones discloses the use of high-sensitivity pixels and low-sensitivity pixels forming the solid-state image pickup, wherein a photometric characteristic of an output of the high-sensitivity pixels being different from that of the low-sensitivity pixels (column 4, lines 3-35, high and low sensitivity pixels are inherently different in photometric characteristic), and by combining this with the Serizawa device, the exposure value is calculated based on values of signal detected by the highsensitivity pixels and values of signal detected by the low-sensitivity pixels. Jones teaches that the use of high-sensitivity pixels and low-sensitivity pixels forming the solidstate image pickup is preferred in order to capture a single image instead of two. thereby reducing the amount of memory needed and to reduce the effects of changes in the scene that occur between capturing the two images (column 1, lines 52-65). Therefore, it would have been obvious to one of ordinary skill in the art to modify the Serizawa device to include the use of high-sensitivity pixels and low-sensitivity pixels forming the solid-state image pickup in order to capture a single image instead of two, thereby reducing the amount of memory needed and to reduce the effects of changes in the scene that occur between capturing the two images, as suggested by Jones.

Page 5

- 3. Claims 2-3 are rejected under 35 U.S.C. 103(a) as being unpatentable over Skow (US PGPub # 20030184659) in view of Jones (US Patent # 6,924,841).
- 4. In regard to claim 2, note Skow discloses the use of an image pickup apparatus, comprising an image pickup means for picking up a subject image (paragraph 0016), received light quantity detecting means having pixels (paragraph 0016, the pixels of the

sensor), and control means for calculating an exposure value based on signal showing received light quantity detected by said pixels, which are output from said received light quantity detecting means in a single instance of photometry, and controlling said image pickup means to pick up a subject image according to the exposure value (paragraphs 0022-0024).

Therefore, it can be seen that the Skow device lacks the use of high-sensitivity pixels and low-sensitivity pixels forming the light quantity detecting means and that the exposure value is calculated based on values of signal detected by the high-sensitivity pixels and values of signal detected by the low-sensitivity pixels, wherein a photometric characteristic of an output of the high-sensitivity pixels being different from that of the low-sensitivity pixels. Jones discloses the use of high-sensitivity pixels and lowsensitivity pixels forming the solid-state image pickup, wherein a photometric characteristic of an output of the high-sensitivity pixels being different from that of the low-sensitivity pixels (column 4, lines 3-35, high and low sensitivity pixels are inherently different in photometric characteristic), and by combining this with the Skow device, the exposure value is calculated based on values of signal detected by the high-sensitivity pixels and values of signal detected by the low-sensitivity pixels. Jones teaches that the use of high-sensitivity pixels and low-sensitivity pixels forming the solid-state image pickup is preferred in order to capture an image having a high dynamic range so that all areas of the image, including light areas and dark areas are captured sufficiently (column 1, lines 28-40). Therefore, it would have been obvious to one of ordinary skill in the art to modify the Skow device to include the use of high-sensitivity pixels and low-

sensitivity pixels forming the solid-state image pickup in order to capture an image having a high dynamic range so that all areas of the image, including light areas and dark areas are captured sufficiently, as suggested by Jones.

5. In regard to claim 3, note Skow discloses the use of a photometer which calculates an exposure value of the image pickup apparatus, comprising received light quantity detecting means having pixels (paragraph 0016) and calculating means for calculating the exposure value based on signal showing received light quantity detected by said pixels, which are output from the received light quantity detecting means in a single instance of photometry (paragraph 0024).

Therefore, it can be seen that the Skow device lacks the use of high-sensitivity pixels and low-sensitivity pixels forming the light quantity detecting means and that the exposure value is calculated based on values of signal detected by the high-sensitivity pixels and values of signal detected by the low-sensitivity pixels, wherein a photometric characteristic of an output of the high-sensitivity pixels being different from that of the low-sensitivity pixels. Jones discloses the use of high-sensitivity pixels and low-sensitivity pixels forming the solid-state image pickup, wherein a photometric characteristic of an output of the high-sensitivity pixels being different from that of the low-sensitivity pixels (column 4, lines 3-35, high and low sensitivity pixels are inherently different in photometric characteristic), and by combining this with the Skow device, the exposure value is calculated based on values of signal detected by the high-sensitivity pixels and values of signal detected by the low-sensitivity pixels. Jones teaches that the use of high-sensitivity pixels and low-sensitivity pixels forming the solid-state image

pickup is preferred in order to capture an image having a high dynamic range so that all areas of the image, including light areas and dark areas are captured sufficiently (column 1, lines 28-40). Therefore, it would have been obvious to one of ordinary skill in the art to modify the Skow device to include the use of high-sensitivity pixels and low-sensitivity pixels forming the solid-state image pickup in order to capture an image having a high dynamic range so that all areas of the image, including light areas and dark areas are captured sufficiently, as suggested by Jones.

Conclusion

The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

US005264940A: note the use of two exposure levels used to calculate a compensated exposure value.

US006219097B1: note the use of two exposure levels used to calculate a compensated exposure value.

US005929908A: note the use of multiple exposure levels used in dynamic range expansion.

US004706123: note the use of pixel level adjustment of exposure timing.

US007024108B2: note the use of two exposure levels used to calculate a compensated exposure value.

US006839087B1: note the use of multiple exposure levels used to calculate a compensated exposure value.

Application/Control Number: 10/618,699 Page 9

Art Unit: 2622

THIS ACTION IS MADE FINAL. Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Chriss S. Yoder, III whose telephone number is (571) 272-7323. The examiner can normally be reached on M-F: 8 - 4:30.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Vivek Srivastava can be reached on (571) 272-7304. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Application/Control Number: 10/618,699

Art Unit: 2622

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

CSY April 25, 2007

> VIVEK SRIVASTAVA SUPERVISORY PATENT EXAMINER TECHNOLOGY CENTER 2600

Page 10